

Patternpro™

ULTRA STABLE PATTERNING FABRIC

Patternpro® has been a favorite material for Australian fabricators for a number of years. Popular as a pattern material for marine and awning projects and can be used for short-term stationary tarps and covers.



Product profile

Material – High Density Polyethylene, Virgin grade

Weight – 4.87 oz per sq yard/165qsm +/-5%

Scrim - 10 x 10 per sq inch

Width - 78.7 inches/2 meters

Roll Length – 55 yards/50 meters (rolled on paper cores)

Color – Translucent (Clear)

Temperature Resistance - ~-22 deg F to +158 deg F/-30 deg C to +70 deg

Technical specification

70%		
Warp	13KN/m	ASTM D 5035
Weft	13KN/m	ASTM D 5035
Tear strength Warp	130 N	ASTM D 751
Weft	130 N	ASTM D 751
Elongation Warp	20%	ASTM D 5035
Weft	20%	ASTM D 5035
	Warp Weft Warp Weft Warp	Warp 13KN/m Weft 13KN/m Warp 130 N Weft 130 N Warp 20%

Product Disclaimers:

This product is designed for patterning or for short-term/temporary covers.

This product is not suitable for applications where excessive flexing or 'wind flap' is present.

The product specifications represent the results sourced from third party testing authorities, and tolerances may vary by as much as +/-10%.

The Manufacturer reserves the right to alter or modify product specifications and colors without notice, and assumes no obligation or liability for the suitability and use of its products other than those applications intended by the Manufacturer.



www.PolyfabUSA.com